

KillTest

質量更高 服務更好



學習資料

<http://www.killtest.net>

一年免費更新服務

Exam : **156-836**

Title : Check Point Certified
Maestro Expert - R81
(CCME)

Version : DEMO

1.What Maestro component is automatically designated the SMO Master?

- A. The SGM with the lowest member ID (the first one added to the security group.)
- B. The MDS that pushes policy to the SMO is considered the SMO Master.
- C. The first MHO configured is considered the SMO Master.
- D. The SGM with the highest member ID (the last one added to the security group.)

Answer: C

Explanation:

In Check Point Maestro's orchestration environment, the Master Orchestrator (MHO) plays a crucial role in managing the Security Group's operation. The first MHO that you configure in a Maestro environment takes on the role of the SMO Master. This MHO is responsible for controlling and managing the entire security environment and ensures all configurations and policies are correctly implemented across the security group.

2.What is a downlink interface used for?

- A. To connect appliances to Orchestrators
- B. To connect appliances to customer's infrastructure
- C. To connect in between Orchestrators
- D. To connect Orchestrators to customer's infrastructure

Answer: B

3.What type of license is required for an MHO?

- A. The MHO requires a NGTP license.
- B. The MHO requires a VSX license.
- C. The MHO does not require a license.
- D. A license is needed for each attached SGM.

Answer: C

Explanation:

The MHO (Maestro Hyperscale Orchestrator) does not require a license by itself, but each SGM (Security Group Module) that is attached to the MHO needs a license. The license type depends on the features and blades that are enabled on the SGM. For example, if the SGM is running VSX, it needs a VSX license.

Reference:

- Maestro Expert (CCME) Course - Check Point Software, page 71
- Check Point Certified Maestro Expert (CCME) R81.X - Global Knowledge, course outline

4.What Maestro component acts as a load balancer and network switch?

- A. Security Switching Module (SSM)
- B. Maestro Hyperscale Orchestrator (MHO)
- C. Security Group (SG)
- D. Security Gateway Module (SGM)

Answer: B

Explanation:

- The Quantum Maestro Orchestrator uses the Distribution Mode to assign incoming traffic to Security Group Members.

- Reference: Working with the Distribution Mode

5.What is an uplink interface used for?

- A. To connect in between appliances
- B. To connect appliances to customer's infrastructure
- C. To connect Orchestrators to customer's infrastructure
- D. To connect in between Orchestrators

Answer: C

Explanation:

Uplink interfaces are used to connect Maestro Hyperscale Orchestrators (MHOs) to the customer's network infrastructure, such as switches, routers, or firewalls. They are also used to send and receive management and control traffic from the customer's network to the MHOs.

Reference:

- Maestro Expert (CCME) Course - Check Point Software, page 41
- Check Point Certified Maestro Expert (CCME) R81.X - Global Knowledge, course outline