KillTest

質量更高　服務更好



練習題

https://www.killtest.net

一年免費更新服務

Exam : **1D0-635**

Title : CIW JavaScript Specialist

Version : Demo

1.Assuming the function <body onload="DisplayName()"> is called, which script block will display Hello Joe in the document window after you enter the name Joe?

A. <script type="text/javascript"
>
function DisplayName(void)
{
var YourName = window.prompt("What is your name?","Please enter your name")
;
document.write("Hello " + YourName)
;
}
</script>

B. <script type="text/javascript"
>
function DisplayName()
{
var YourName = window.prompt("What is your name?","Please enter your name")
;
document.write("Hello " + YourName)
;
}
</script>

C. <script type="text/javascript"
>
function DisplayName(void)
{
var YourName = document.prompt("What is your name?",Please enter your name)
;
document.write("Hello " + YourName)
;
}
</script>

D. <script type="text/javascript"
>
function DisplayName()
{
var YourName = document.prompt("What is your name?","Please enter your name")
;
document.write("Hello " + yourname)
;
}
</script>

Answer: B

2.Consider the following code fragment, which sets up the retrieval of an XML document named fish.xml and calls a function named showFish(): var xmlhttp = new XMLHttpRequest(); xmlhttp.open("GET", "fish.xml", true); xmlhttp.onreadystatechange = showFish(); xmlhttp.send();
Which line of code initializes the XMLHttpRequest object.?
A. xmlhttp.send();
B. var xmlhttp = new XMLHttpRequest();
C. xmlhttp.open("GET", "fish.xml", true);
D. xmlhttp.onreadystatechange = showFish();
Answer: C

3.Which of the following demonstrate the correct syntax for the switch statement?
A. var myName= "Paul"
switch (myName)
{
case "Peter"
document.write("My name is Peter.
"
)
break
case "Paul"
document.write("My name is Paul.
"
)
break: (default)
;
document.write("I do not have a name.
"
)
}
B. var myName= "Paul"
switch (myName)
{
case "Peter"
document.write("My name is Peter.
"
)
break
case "Paul"
document.write("My name is Paul.
"
)
break: (default)
;
document.write("I do not have a name.
"
)
}
C. var myName= "Paul"
switch (myName)
{

```
case (Peter)
document.write("My name is Peter.<br />"
)
break
case (Paul)
document.write("My name is Paul.<br />"
)
break;
case: (default)
;
document.write("I do not have a name.<br />"
)
}
```

D.

```
var myName= "Paul"
switch (myName)
{
case (Peter)
document.write("My name is Peter.<br />"
)
break
case (Paul)
document.write("My name is Paul.<br />"
)
break;
case: (default)
;
document.write("I do not have a name.<br />"
)
}
```

Answer: A

4.Consider the following code: <script type="text/javascript"> var v1 = "alpha"; function f () { var v2 = "bravo"; alert (v1 + ", " + v2); } f(); v1="charlie"; alert (v1 + ", " + v2); </script> What is the expected result when you run this script in the browser?

A. An alert box displaying charlie, bravo

B. An alert box displaying alpha, bravo followed by an error

C. Two alert boxes displaying alpha, bravo and alpha, bravo respectively

D. Two alert boxes displaying alpha, bravo and charlie, bravo respectively, followed by an error

Answer: B

5.Which of the following is a valid variable name in JavaScript?

A. this

B. that

C. 2that

D. 2this
Answer: B