

KillTest

質量更高 服務更好



練習題

<https://www.killtest.net>

一年免費更新服務

Exam : FCSS_SASE_AD-24

**Title : FCSS - FortiSASE 24
Administrator**

Version : DEMO

1.Refer to the exhibits.

Web Filtering logs

User	Destination P...	Traffic Type	Security Events	Security Action	Log Details
☒ user2@fortinettraining.lab	443	Internet Access	Web Filter	Allowed	Details Security
☐ user2@fortinettraining.lab	443	Internet Access	Web Filter	Allowed	Agent Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/122.0.0.0 Safari/537.36
☐ user2@fortinettraining.lab	443	Internet Access	Web Filter	Allowed	Category 50
☐ user2@fortinettraining.lab	443	Internet Access	Web Filter	Allowed	Category Description Information and Computer Security
☐ user2@fortinettraining.lab	443	Internet Access	Web Filter	Allowed	Direction outgoing
☐ user2@fortinettraining.lab	443	Internet Access	Web Filter	Allowed	Event Type ftgd_allow
☐ user2@fortinettraining.lab	443	Internet Access	Web Filter	Allowed	Hostname www.eicar.org
☐ user2@fortinettraining.lab	443	Internet Access	Web Filter	Allowed	Message URL belongs to an allowed category in policy
☐ user2@fortinettraining.lab	443	Internet Access	Web Filter	Allowed	Profile Group SIA (Internet Access)
☐ user2@fortinettraining.lab	443	Internet Access	Web Filter	Allowed	Referrer URI https://www.eicar.org/download-anti-malware-testfile/
☐ user2@fortinettraining.lab	443	Internet Access	Web Filter	Allowed	Request Type referral
☐ user2@fortinettraining.lab	443	Internet Access	Web Filter	Allowed	Sub Type webfilter
☐ user2@fortinettraining.lab	443	Internet Access	Web Filter	Allowed	Type utm
☐ user2@fortinettraining.lab	443	Internet Access	Web Filter	Allowed	Timezone -0800
☐ user2@fortinettraining.lab	443	Internet Access	Web Filter	Allowed	URL https://www.eicar.org/download/eicar_com-zip/?vpdm=8847&refresh=65df3477aba001709126775

Security Profile Group

Rename Delete Antivirus Threats Count Inspected Protocols HTTP SMTP POP3 IMAP FTP CIFS View All View Logs Customize	Web Filter With Inline-CASB Threats Count Filters www.eicar.org 5f3c395.com19.de www.eicar.com encrypted-tbn0.gstatic.com ocsp.digicert.com Allow Block Exempt Monitor Warning Disable Inline-CASB Headers View All View Logs Customize
Intrusion Prevention Threats Count Intrusion Prevention Recommended Scanning traffic for all known threats and applying the recommended actions. Disabled View All View Logs Customize	SSL Inspection Threats Count SSL Inspection ssl-anomaly Deep Inspection SSL connections are decrypted to allow for inspection of the contents. Exempt Hosts Exempt URL Categories View All View Logs Customize

Secure Internet Access policy

Name	Web Traffic
Source Scope	All VPN Users Edge Device
Source	All Traffic Specify
User	All VPN Users Specify
	VPN_Users +
Destination	All Internet Traffic Specify
Service	ALL +
Profile Group	Default Specify
	SIA
Force Certificate Inspection	☒
Action	Accept Deny
Status	Enable Disable
Logging Options	
Log Allowed Traffic	☒ Security Events All Sessions

A FortiSASE administrator has configured an antivirus profile in the security profile group and applied it to the internet access policy. Remote users are still able to download the eicar.com-zip file from <https://eicar.org>. Traffic logs show traffic is allowed by the policy.

Which configuration on FortiSASE is allowing users to perform the download?

- A. Web filter is allowing the traffic.
- B. IPS is disabled in the security profile group.
- C. The HTTPS protocol is not enabled in the antivirus profile.
- D. Force certificate inspection is enabled in the policy.

Answer: D

Explanation:

<https://community.fortinet.com/t5/FortiSASE/Technical-Tip-Force-Certificate-Inspection-option-in-FortiSASE/ta-p/302617>

2.An organization wants to block all video and audio application traffic but grant access to videos from

CNN.

Which application override action must you configure in the Application Control with Inline-CASB?

- A. Allow
- B. Pass
- C. Permit
- D. Exempt


Answer: A

Explanation:

(<https://docs.fortinet.com/document/fortisase/24.4.75/sia-agent-based-deployment-guide/568255/configuring-application-control-profile>)

3.Refer to the exhibits.

Topology



Priority settings

Set Priority ▾		Ashburn - Virginia - USA ▾	
☐	Name	Priority ▴	
☐	HUB-1	P1	(Highest Priority)
☐	HUB-2	P2	

When remote users connected to FortiSASE require access to internal resources on Branch-2. how will traffic be routed?

- A. FortiSASE will use the SD-WAN capability and determine that traffic will be directed to HUB-2. which will then route traffic to Branch-2.
- B. FortiSASE will use the AD VPN protocol and determine that traffic will be directed to Branch-2 directly, using a static route
- C. FortiSASE will use the SD-WAN capability and determine that traffic will be directed to HUB-1, which will then route traffic to Branch-2.

D. FortiSASE will use the AD VPN protocol and determine that traffic will be directed to Branch-2 directly, using a dynamic route

Answer: D

4.What are two advantages of using zero-trust tags? (Choose two.)

- A. Zero-trust tags can be used to allow or deny access to network resources
- B. Zero-trust tags can determine the security posture of an endpoint.
- C. Zero-trust tags can be used to create multiple endpoint profiles which can be applied to different endpoints
- D. Zero-trust tags can be used to allow secure web gateway (SWG) access

Answer: A,B

Explanation:

Zero-trust tags are critical in implementing zero-trust network access (ZTNA) policies. Here are the two key advantages of using zero-trust tags:

Access Control (Allow or Deny):

Zero-trust tags can be used to define policies that either allow or deny access to specific network resources based on the tag associated with the user or device.

This granular control ensures that only authorized users or devices with the appropriate tags can access sensitive resources, thereby enhancing security. **Determining Security Posture:**

Zero-trust tags can be utilized to assess and determine the security posture of an endpoint. Based on the assigned tags, FortiSASE can evaluate the device's compliance with security policies, such as antivirus status, patch levels, and configuration settings.

Devices that do not meet the required security posture can be restricted from accessing the network or given limited access.

Reference: FortiOS 7.2 Administration Guide: Provides detailed information on configuring and using zero-trust tags for access control and security posture assessment.

FortiSASE 23.2 Documentation: Explains how zero-trust tags are implemented and used within the FortiSASE environment for enhancing security and compliance.

5.Refer to the exhibit.



In the user connection monitor, the FortiSASE administrator notices the user name is showing random characters.

Which configuration change must the administrator make to get proper user information?

- A. Turn off log anonymization on FortiSASE.
- B. Add more endpoint licenses on FortiSASE.
- C. Configure the username using FortiSASE naming convention.
- D. Change the deployment type from SWG to VPN.

Answer: A

Explanation:

In the user connection monitor, the random characters shown for the username indicate that log anonymization is enabled. Log anonymization is a feature that hides the actual user information in the logs for privacy and security reasons. To display proper user information, you need to disable log anonymization.

Log Anonymization:

When log anonymization is turned on, the actual usernames are replaced with random characters to protect user privacy.

This feature can be beneficial in certain environments but can cause issues when detailed user monitoring is required.

Disabling Log Anonymization:

Navigate to the FortiSASE settings.

Locate the log settings section.

Disable the log anonymization feature to ensure that actual usernames are displayed in the logs and user connection monitors.

Reference: FortiSASE 23.2 Documentation: Provides detailed steps on enabling and disabling log anonymization.

Fortinet Knowledge Base: Explains the impact of log anonymization on user monitoring and logging.